

Airworthiness Directive

▶ Federal Register Information

▼ Header Information

DEPARTMENT OF TRANSPORTATION

Federal Aviation Administration

14 CFR Part 39

AD 49-14-01

Airworthiness Directives; Piper Model J3 Series, PA-11, and PA-12, All Airplanes
PDF Copy (If Available):

▼ Preamble Information

AGENCY: Federal Aviation Administration, DOT

▼ Regulatory Information

49-14-01 PIPER: Applies to Model J3 Series, Serial Numbers 14027 and Up; PA-11, Serial Numbers 11-1 to 11-910; and PA-12, All Airplanes.

To be accomplished by April 20, 1949.

Inspect the fittings (P/N 40861) at each end of the elevator connector tube (P/N 40261) to determine if the end fittings are riveted to the tube with two rivets 90 degrees apart. If not, attach the end fitting to the tube with two 1/8-inch diameter, 3/4-inch long soft steel, flat or round head rivets 90 degrees apart; or replace with a new connector tube assembly. Full forward position of the control stick will expose the rearward fitting and full rearward position of the stick will expose the forward fitting.

(Piper Service Bulletin No. 111 covers the same subject.)

▼ **Footer Information**

▼ **Comments**

FAA.gov Home | Privacy Policy | Web Policies & Notices | Contact Us | Help

Readers & Viewers: [PDF Reader](#) | [MS Word Viewer](#) | [MS PowerPoint Viewer](#) | [MS Excel Viewer](#) | [WinZip](#)